



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
02.02.2000 Bulletin 2000/05

(51) Int. Cl.⁷: **A61M 25/01**

(21) Application number: **99114286.0**

(22) Date of filing: **29.07.1999**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **31.07.1998 US 127222**

(71) Applicant: **Zuli Holdings Ltd.**
47226 Ramat Hasharon (IL)

(72) Inventor: **Richter, Jacob**
Ramat Hasharon 47226 (IL)

(74) Representative:
Altenburg, Udo, Dipl.-Phys. et al
Patent- und Rechtsanwälte
Bardehle . Pagenberg . Dost . Altenburg .
Geissler . Isenbruck
Galileiplatz 1
81679 München (DE)

(54) **Apparatus and method for selctively positioning a device and manipulating it**

(57) Apparatus for pulling and positioning an apparatus, e.g., a stent, in the target area of a lumen. In one embodiment, a cylindrically shaped motor has a longitudinal bore, a friction area within the longitudinal bore, and a guide wire disposed within the longitudinal bore. The guide wire and friction area of the motor are sized and adapted to contact each other and impart friction between the friction area and the guide wire to permit the motor to pull a catheter to the target area by crawling against the guide wire. In another embodiment, a cylindrical motor having a friction area on its outer surface is disposed within a guide tube.




FIG. 1

Description

FIELD OF THE INVENTION

[0001] This invention relates generally to an apparatus and method of selectively positioning the apparatus, e.g., within a lumen. More particularly, this invention relates to a device and method for pulling a catheter along a wire; a device and method for moving a wire relative to a catheter, a device and method for pulling a catheter relative to a guiding catheter or any larger bore pipeline through which it is inserted; and a device and method for pushing or pulling a device on top of a guide wire or inside a guiding catheter.

BACKGROUND OF THE INVENTION

[0002] In many different applications of invasive and minimally invasive medicine there is a need to introduce catheters and other devices into the body, usually through open lumens or closed lumens, utilizing percutaneous entry. Conventional procedures for the introduction of the devices and their controlled motion in the body usually utilize a force, either a manual force or a motorized force, applied from the outside of the patient to "push" the device to the target area. One shortcoming of introducing the device via a "push" operation, even when done on top of a guiding wire, is that this procedure often does not provide optimal tractability into a tortuous anatomy, e.g., the coronary arteries. In contrast, a "pull" operation in which a pulling device precedes the apparatus and "pulls" it into place increases the tractability of the device and reduces the likelihood that the device will get caught in a curve of the lumen or cause trauma to the lumen.

[0003] Another problem is the need to push wires through occluded lumen sections that have a great resistance to such penetration. The fact that the wire is pushed from the outside may waste all the pushing energy in accessive loops with very little or none of the pushing energy actually reaching the tip of the wire.

OBJECTS AND SUMMARY OF THE INVENTION

[0004] It is an object of this invention to provide a device and method for pulling a catheter along a wire.

[0005] It is another object of this invention to provide a device and method for pushing a wire relative to a catheter.

[0006] In yet another object of this invention to provide a device and method for pulling a catheter relative to a guiding catheter or any larger bore pipeline through which it is inserted.

[0007] It is a further object of this invention to provide a device and method for pushing or pulling a device on top of a guidewire or inside a guiding catheter.

[0008] It is still a further object of this invention to provide an apparatus and method for selectively position-

ing a device, e.g., a stent, an Intra Vascular Sound (IVUS) transducer, an atherectomy device (both rotational and directional), pressure sensors, balloons, and pushing wires to open occlusions, by pulling rather than pushing these devices into place.

[0009] It is an object of this invention to provide an apparatus for disposing a device in the target area of a lumen, preferably comprising: a motor attached to the device, the motor having a longitudinal bore, the motor provided with a motor friction area disposed within the longitudinal bore; a guide wire disposed within the longitudinal bore, the guide wire and the longitudinal bore sized and adapted to impart friction between the friction area of the motor and the guide wire in an amount sufficient to permit the motor to change position relative to the guide wire by crawling against the guide wire when the motor is energized.

[0010] It is another object of this invention to provide an apparatus for disposing a device in the target area of a lumen, preferably comprising: a motor attached to the device, the motor having an outer surface, the motor provided with a friction area on the outer surface; a cylindrical guide tube having an outer surface and an inner surface defining a longitudinal bore, the outer surface of the motor and the inner surface of the guide tube sized and adapted to impart friction between the friction area of the motor and the inner surface of the cylindrical guide tube in an amount sufficient to permit the motor to change position relative to the guide tube by crawling against the inner surface of the guide tube when the motor is energized.

[0011] It is still another object of this invention to provide an apparatus for disposing a stent in the target area of a lumen, preferably comprising: a catheter having a proximal end, a distal end, a longitudinal bore therethrough, and an expandable balloon disposed at the distal end; a motor disposed at the distal end of the catheter distal to the balloon, the motor having a longitudinal bore communicating with the longitudinal bore of the catheter, the motor provided with a motor friction area disposed within the longitudinal bore; a guide wire disposed within the longitudinal bore of the catheter and the longitudinal bore of the motor, the guide wire and the longitudinal bore of the motor sized and adapted to impart friction between the friction area of the motor and the guide wire in an amount sufficient to permit the motor to change position relative to the guide wire by crawling against the guide wire when the motor is energized.

[0012] It is another object of this invention to provide a method of disposing a stent in the target area of a lumen, preferably comprising the steps of:

- a) constructing an apparatus comprising: a catheter having a proximal end, a distal end, a longitudinal bore therethrough, and an expandable balloon disposed at the distal end; a motor disposed at the distal end of the catheter dis-

tal to the balloon, the motor having a longitudinal bore communicating with the longitudinal bore of the catheter, the motor provided with a motor friction area disposed within the longitudinal bore, a guide wire disposed within the longitudinal bore of the catheter and the longitudinal bore of the motor, the guide wire and the longitudinal bore of the motor sized and adapted to impart friction between the friction area of the motor and the guide wire in an amount sufficient to permit the motor to change position relative to the guide wire by crawling against the guide wire when the motor is energized;

b) advancing the guide wire to the target area;

c) securing the guide wire;

d) energizing the motor so that it advances along the guide wire to the target area to dispose the stent in the target area of lumen;

e) inflating the balloon to secure the stent in the target area of the lumen;

f) deflating the balloon; and

g) withdrawing the guide wire, motor, and catheter from the lumen.

[0013] It is yet another object of this invention to provide a method of disposing a stent in an obstructed target area of a lumen, preferably comprising the steps of:

a) constructing an apparatus comprising: a catheter having a proximal end, a distal end, a longitudinal bore therethrough, and an expandable balloon disposed at the distal end; a motor disposed at the distal end of the catheter distal to the balloon, the motor having a longitudinal bore communicating with the longitudinal bore of the catheter, the motor provided with a motor friction area disposed within the longitudinal bore, a guide wire disposed within the longitudinal bore of the catheter and the longitudinal bore of the motor, the guide wire and the longitudinal bore of the motor sized and adapted to impart friction between the friction area of the motor and the guide wire in an amount sufficient to permit the motor to change position relative to the guide wire by crawling against the guide wire when the motor is energized;

b) advancing the guide wire to the target area;

c) securing the guide wire;

d) energizing the motor so that the motor advances along the guide wire to the obstructed target area;

e) securing the catheter;

f) energizing the motor so that the guide wire advances through the longitudinal bore of the motor and into the obstructed target area of the lumen;

g) securing the guide wire;

h) energizing the motor so that the motor advances along the guide wire and disposes the stent in the target area of the lumen;

i) inflating the balloon to secure the stent in the target area of the lumen;

j) deflating the balloon; and

k) withdrawing the guide wire, motor, and catheter from the lumen.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

FIG. 1 shows an embodiment of the invention in which a cylindrically shaped motor and a guide wire are utilized to dispose a device in the target area of a lumen;

FIG. 2 is a cross-sectional end view of the embodiment of the invention shown in FIG. 1;

FIG. 3 shows an embodiment of the invention in which a cylindrical motor and a cylindrical guide tube are used to dispose a device in the target area of a lumen;

FIG. 4 shows a cross-sectional side view of another embodiment of the invention shown in FIG. 3;

FIG. 5 shows the tractability of a catheter that is pulled through a curve in a lumen in accordance with the present invention;

FIG. 6 shows the tractability of a catheter that is pushed through a curve in a lumen in a conventional manner;

FIG. 7 shows an embodiment of the invention used to dispose a balloon expandable stent in the lumen of a blood vessel;

FIGS. 8A to 8D shows an embodiment of the invention used to clear an obstructed lumen; and

FIG. 9 shows an alternative embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0015] Miniature Oscillating Ceramic Motors (OCM) are well known in the art and are disclosed in U.S. patent 5,453,653 to Zumeris the specification of which is incorporated herein by reference. These motors can be made very small and in any shape and they operate by contacting a surface in an amount sufficient to generate sufficient friction to permit the motor to "crawl" along the contacted surface and change its position relative to the contacted surface when the motor is energized. These motors can be adequately insulated to act in aqueous environments. Their small size and low energy level requirements make them especially suitable for use inside living organisms.

[0016] FIG. 1 is a lateral perspective of one embodiment of the invention and shows a cylindrical motor 1 having a longitudinal bore therethrough. A guide wire 2 is disposed within the longitudinal bore 5. FIG. 2 is a cross-sectional end view taken on line A-A of FIG. 1 and shows the cylindrical motor 1 having an outer surface 3 and an inner surface 4 defining a longitudinal bore 5. The inner surface 4 defining the longitudinal bore 5 is provided with a friction area 6 adapted to engage the

guide wire 2. The longitudinal bore 5 and the guide wire 2 are sized and adapted so that when the motor 1 is energized the motor 1 will crawl along the guide wire 2, thus, changing its position relative to the guide wire 2. The direction of movement is controlled selectively by energizing wires (not shown) connected to the motor 1. In one embodiment, shown in FIG. 2, a biasing means, e.g., a leaf spring 7 is utilized to bias the guide wire 2 against the friction area 6 of the motor 1.

[0017] FIG. 3 is a cross-sectional side view of another embodiment of the invention and shows a cylindrical motor 8 having an external surface 10 mounted within a guide tube 9 having an outer surface 11 and an inner surface 12. The external surface 10 of the motor 8 and the inner surface 12 of the guide tube 9 are sized and adapted so that the friction area 14 of the motor 8 contacts the inner surface 12 of the guide tube 9 and crawls along the inner surface 12 so as to dispose a device, e.g., an Intra Vascular Ultra Sound (IVUS) transducer, atherectomy device, or physiological sensor, (not shown) in the target area of a lumen. In an especially preferred embodiment, shown in FIG. 4, a leaf spring 13 is utilized to bias the friction surface 14 of the motor 8 against the internal surface 12 of the guide tube 9.

[0018] In another embodiment of this invention, shown in FIG. 7, a balloon catheter with a micro-motor disposed at the distal end is used to dispose an expandable stent in the target area of a lumen. FIG. 7 shows a catheter 15 having a proximal end 16, a distal end 17, and a longitudinal bore 18 therethrough. An expandable balloon 19 is disposed at the distal end 17. A cylindrically shaped motor 1 is disposed at the distal end 17 of the catheter 15 distal to the balloon 19. The motor 1 has a longitudinal bore 5 communicating with the longitudinal bore 18 of the catheter 15 and is provided with a motor friction area 6 disposed within the longitudinal bore 5 of the motor 1. A guide wire 2 is disposed within the longitudinal bore 18 of the catheter 15 and the longitudinal bore 5 of the motor 1. The guide wire 2 and the longitudinal bore 5 of the motor 1 are sized and adapted to impart friction between the friction area 6 of the motor 1 and the guide wire 2 in an amount sufficient to permit the motor 1 to change position relative to the guide wire 2 by crawling against the guide wire 2 when the motor 1 is energized.

[0019] In operation, an expandable stent 20 is secured to the balloon portion 19 of the catheter 15 and the guide wire 2 is placed into the bore 18 of the catheter 15. The guide wire 2 is then introduced into the lumen to be treated and is advanced by pushing it until it is near the target area. The guide wire 2 is then secured. The micro-motor 1 is then energized so that it crawls along the guide wire 2 which pulls the catheter 15 into the proximity of the target area to be treated. Because the catheter 15 is "pulled" into position as shown in FIG. 5, there is improved tractability and less kinking of the catheter 15, and, thus, reduced risk of trauma to the internal surface of the lumen than when the catheter is

"pushed" into place using conventional procedures as shown in FIG. 6. The balloon 19 is then expanded to secure the stent 20 in the target area of the lumen. The balloon 19 is then deflated and the guide wire 2 and the catheter 15 are pulled out of the lumen using conventional methods.

[0020] In another embodiment of this invention shown in FIGS. 8A to 8D, the motor is used to push the guide wire into, and if specific applications dictate through, a constricted area which clears the vessel of the obstruction to permit the catheter to advance beyond the obstruction to the target area. In operation, the catheter 15 is mounted on a guide wire 2 as previously discussed. The guide wire 2 is advanced to the obstruction 21 as shown in FIG. 8A. The guide wire 2 is secured and the motor is energized causing the catheter to advance towards the obstruction 21. The catheter 15 is advanced until it too is in proximity to the obstruction 21 as shown in FIG. 8B. The catheter 15 is then secured and the motor 1 is activated which causes the guide wire 2 to advance into the obstructed area 21 as shown in FIG. 8C. In some applications, one or more passes may be utilized to clear the obstruction 21. The guide wire 2 is then secured, the motor 1 is energized, and the catheter 15 is advanced through the vessel past the area from which the guide wire 2 has cleared the obstruction 21 from the target area as shown in FIG. 8D. This method may be used to simply clear an obstruction in a lumen as discussed above or may be used in conjunction with other embodiments of the invention, e.g., to facilitate the placement of an expandable stent in the target area of a lumen by first clearing the target area of any obstructions.

[0021] FIG. 9 shows an alternative embodiment of the invention and shows a slab-shaped motor 22 incorporated in a catheter 23. In the embodiment shown in FIG. 9, the motor 22 is shaped like a slab instead of being cylindrical. The slab-shaped motor 22 is disposed on the inner wall of the catheter 23 and is provided with a friction area 6 sized and adapted to frictionally engage a guide-wire 2. The slab-shaped motor 22 is sized and adapted to permit the catheter 23 to be moved relative to the guide-wire 2 as previously discussed and as shown in FIG. 9.

[0022] While the invention has been described with respect to a limited number of embodiments, it will be appreciated that many variations, modifications, and other applications of the invention may be made.

Claims

1. An apparatus for disposing a device in the target area of a lumen, comprising: a motor adapted to be attached to said device, said motor having a longitudinal bore, said motor provided with a motor friction area disposed within said longitudinal bore; a guide wire disposed within said longitudinal bore, said guide wire and said longitudinal bore sized and

adapted to impart friction between said friction area of said motor and said guide wire in an amount sufficient to permit said motor to change position relative to said guide wire by crawling against said guide wire when said motor is energized.

5

2. The apparatus of Claim 1, further comprising a biasing means to bias said guide wire against said friction area.

10

3. The apparatus of Claim 2, wherein said biasing means is a leaf spring.

4. The apparatus of any one of Claims 1 to 3, further comprising:

15

means for advancing said guide wire to said target area;

means for securing said guide wire;

means for energizing said motor so that said motor can advance along said guide wire to said target area to dispose said device in said target area of said lumen; and

means for withdrawing said guide wire, motor and device from said lumen.

20

25

5. An apparatus for disposing a device in the target area of a lumen, comprising: a motor adapted to be attached to said device, said motor having an outer surface, said motor provided with a friction area on said outer surface; a guide tube having an outer surface and an inner surface defining a longitudinal bore, said outer surface of said motor and said inner surface of said guide tube sized and adapted to impart friction between said friction area of said motor and said inner surface of said guide tube in an amount sufficient to permit said motor to change position relative to said guide tube by crawling against said inner surface of said guide tube when said motor is energized.

30

35

40

6. The apparatus of Claim 5, further comprising a biasing means to bias said inner surface of said guide tube against said friction area.

45

7. The apparatus of Claim 6, wherein said biasing means is a leaf spring.

8. The apparatus of any one of Claims 5 to 7, further comprising:

50

means for advancing said guide tube to said target area;

means for securing said guide tube; means for inserting said motor attached to said device in said bore of said guide tube;

55

means for energizing said motor so that said motor can advance along said inner surface of

said guide tube to said target area to dispose said device in said target area of said lumen; and

means for withdrawing said guide tube, motor, and device from said lumen.

9. An apparatus for disposing a stent in the target area of a lumen, comprising: a catheter having a proximal end, a distal end, a longitudinal bore there-through, and an expandable balloon disposed at said distal end; a motor disposed at said distal end of said catheter distal to said balloon, said motor having a longitudinal bore communicating with said longitudinal bore of said catheter, said motor provided with a motor friction area disposed within said longitudinal bore of said motor; a guide wire disposed within said longitudinal bore of said catheter and said longitudinal bore of said motor, said guide wire and said longitudinal bore of said motor sized and adapted to impart friction between said friction area of said motor and said guide wire in an amount sufficient to permit said motor to change position relative to said guide wire by crawling against said guide wire when said motor is energized.

10. The apparatus of Claim 9, further comprising a biasing means to bias said guide wire against said friction area.

11. The apparatus of Claim 10, wherein said biasing means is a leaf spring.

12. The apparatus of any one of Claims 9-11, further comprising:

means for advancing said guide wire to said target area; means for securing said guide wire;

means for energizing said motor so that it can advance along said guide wire to said target area to dispose said stent in said target area of said lumen;

means for inflating said balloon to secure said stent in said target area of said lumen;

means for deflating the balloon; and

means for withdrawing said guide wire, motor, and catheter from said lumen.

13. The apparatus of any one of Claims 9-11, further comprising:

means for advancing said guide wire to said target area;

means for securing said guide wire; means for energizing said motor so that said motor can advance along said guide wire to said obstructed target area;

means for securing said catheter; means for

energizing said motor so that said guide wire can advance through said longitudinal bore of said motor and into said obstructed target area of said lumen;

means for securing said guide wire; means for energizing said motor so that said motor can advance along said guide wire and dispose said stent in said target area of said lumen; means for inflating said balloon to secure said stent in said target area of said lumen; means for deflating said balloon; and means for withdrawing said guide wire, motor, and catheter from said lumen.

14. Medical apparatus comprising: a tubular catheter having a longitudinal bore; a guide wire disposed within the longitudinal bore; and a motor disposed on the inner wall of the catheter and provided with a motor friction area engaging the guide wire such that the motor and catheter can change position relative to the guide wire by crawling against the guide wire when the motor is energized.
15. Medical apparatus substantially as described herein, with reference to the accompanying drawings.

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 5




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9



European Patent
Office

PARTIAL EUROPEAN SEARCH REPORT

Application Number

which under Rule 45 of the European Patent Convention shall be considered, for the purposes of subsequent proceedings, as the European search report

EP 99 11 4286

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	DE 43 29 162 A (STM MEDTECH STARNBERG) 2 March 1995 (1995-03-02) * the whole document *	1,5,9,14	A61M25/01
A	US 5 628 719 A (LAFONTAINE DANIEL M ET AL) 13 May 1997 (1997-05-13) * abstract; figures *	1,5,9,14	
A	US 5 499 632 A (HILL III E RICHARD ET AL) 19 March 1996 (1996-03-19) * abstract; figures *	1,5,9,14	
A	EP 0 541 258 A (IMAGYN MEDICAL INC) 12 May 1993 (1993-05-12) * abstract; figures *	1,5,9,14	
A	WO 95 32539 A (KINETRON BV ;KNAPEN PETRUS MATHEUS JOSEPHUS (NL); MEYER BERNARDUS) 30 November 1995 (1995-11-30) * abstract; figures *	1,5,9,14	
P,A	GB 2 328 877 A (INTRAVASCULAR RES LTD) 10 March 1999 (1999-03-10) * abstract; figures *	1,5,9,14	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A61M A61B H01L
INCOMPLETE SEARCH The Search Division considers that the present application, or one or more of its claims, does/do not comply with the EPC to such an extent that a meaningful search into the state of the art cannot be carried out, or can only be carried out partially, for these claims. Claims searched completely : 1-14 Claims searched incompletely : Claims not searched : 15 Reason for the limitation of the search: Article 29 (6) Claims rely on references to the description or drawings			
Place of search		Date of completion of the search	Examiner
THE HAGUE		2 November 1999	Kousouretas, I
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C07)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 11 4286

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02-11-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4329162 A	02-03-1995	AU 7691994 A	22-03-1995
		CA 2170729 A	09-03-1995
		CN 1132469 A	02-10-1996
		DE 4496456 D	31-07-1997
		WO 9506428 A	09-03-1995
		EP 0740522 A	06-11-1996
		JP 9504449 T	06-05-1997
US 5628719 A	13-05-1997	US 5823199 A	20-10-1998
US 5499632 A	19-03-1996	US 5919161 A	06-07-1999
EP 0541258 A	12-05-1993	US 5389100 A	14-02-1995
		AU 657798 B	23-03-1995
		AU 2638392 A	13-05-1993
		CA 2080535 A	07-05-1993
		DE 69216209 D	06-02-1997
		DE 69216209 T	17-04-1997
		JP 2669515 B	29-10-1997
		JP 5208051 A	20-08-1993
		US 5346498 A	13-09-1994
WO 9532539 A	30-11-1995	NL 9400849 A	02-01-1996
GB 2328877 A	10-03-1999	WO 9912474 A	18-03-1999